



Fonda Speedway 2020 Sunoco Modified Specifications

The 2020 Sunoco Modified division at Fonda Speedway will work off the general guidelines of the Bob Hilbert Sportswear Short Track Super Series (STSS) Fueled By Sunoco. Visit www.shorttracksuperseries.com to see complete regulations.

Engines:

Big- and small-block engine combinations are permitted at Fonda Speedway. Steel-block only (exceptions can be made for W-16, LS and spec combinations). No small-block engine may exceed 450 cubic inches. No big-block engine may exceed 477 cubic inches. Must be (single) carbureted; no fuel injection.

- Big-Block/Small-Block (larger than 363 c.i.): 2,500 lbs.
- Small-Block (363 c.i. – max tolerance 370 c.i.): 2,400 lbs.
- DIRTcar/PA/NJ-legal spec small-block engines (open carb, no rev limiter): 2,350 lbs.
- CT 525 & W-16: 2,300 lbs.

**All weights are track-scale pounds, with driver, post-race. No tolerance.*

Weights are subject to change by Fonda Speedway officials to maintain competitive balance.

Tires:

Right-Rear: American Racer SD 50 compound ONLY

Left-Rear: American Racer SD 48 compound ONLY

Right-Front: American Racer SD 48 compound ONLY

Left-Front: Any American Racer Modified tire

Bodies:

Door heights are as follows: maximum height of 41 inches on the left side and 40 inches on the right.

Left-Side Measurement Points:

16 inches forward from centerline of rear axle: 45 inches maximum, 37 inches minimum

60 inches forward from centerline of rear axle: 41 inches maximum, 36 inches minimum

Right-Side Measurement Points:

16 inches forward from centerline of rear axle: 44 inches maximum, 36 inches minimum

60 inches forward from centerline of rear axle: 40 inches maximum, 35 inches minimum

There cannot be more than a one-inch difference from left door to right door in split.

Rear spoiler rule maximum height: 50 inches. Minimum ground clearance of 6 inches in door skirting and 8-inch minimum for rear quarter-panel skirting.

All other measurements are to mirror the DIRTcar/WRG rule book.

Fuel:

Gasoline only. Sunoco Race Fuels (110, 112 or HCR) are the preferred fuels of Fonda Speedway.